

10 Generating Javadocs; HashMap: Overriding 'equals'

Goals

The first part of the lab you will learn how to generate *Javadoc* documentation, and practice reading *Javadoc* style documentation for programs.

In the second part we will both learn how to define the `equals` method, as well as how to use the `HashMap` data structure defined in the *Java Collections Frameworks*.

10.1 Documentation

For this lab download the following files:

- The file *Balloon.java* — our sample data class
- The file *TopThree.java* will be used to practice working with `ArrayList` in imperative style (using mutation).
- The *Examples.java* file that defines examples of all data and defines all tests.

Create a new **Project** *Lab10* and import into it all files from the zip file. Import the `tester.jar` and `colors.jar`.

Generating Documentation

- Once Eclipse shows you that there are no errors in your files select **Generate Javadoc...** from the **Project** pull-down menu. Select to generate docs for all files in your project with the destination *Lab9/doc* directory. Make sure you select all files for which you wish to generate the documentation.

You should be able to open the *index.html* file in the *Lab10/doc* directory and see the documentation for this project. Compare the documentation for the class `Balloon` with the web pages. You see that all comments from the source file have been converted to the web document.

Observe the format of the comments, especially the `/**` at the beginning of the comment. If you do not understand the rules, ask the TA or one of the tutors, or experiment with new comments. From now on all of your work should have a proper Javadoc style documentation.

- Now use the documentation to see what are the fields in various classes and what methods have been defined already.
- Define a method `isHit` in the class `Balloon` that determines whether a shot aimed at the given `x` and `y` coordinate hits this `Balloon`. Add documentation in the `Javadoc` style. Of course, add tests in the `Examples` class. Run the tests, then rebuild the `Javadocs` and make sure your documentation shows up correctly.

10.2 HashMap and JUnit

Ultimately, the goal of this part of the lab is to learn to use the professional test harness JUnit. It is completely separated from the application code. It is designed to report not only the cases when the result of the test differs from the expected value, but also to report any exceptions the program would throw. The slight disadvantage is that it uses the Java `equals` method that by default only checks for the instance identity. To use the JUnit for the method tests similar to those we have done before we need to *override* the `equals` any time we wish to compare two instances of a class in a manner different from the strict instance identity.

However, each time we override the `equals` method we should make sure that the `hashCode` method is changed in a compatible way. That means that if two instances are `equal` under our definition of `equals` then the `hashCode` method for both instances must produce the same value.

We start with learning to use `HashMap` class. We then see how we can override the needed `hashCode` method. Finally, we also override the `equals` method to implement the equality comparison that best suits our problem.

Part 1: Using the HashMap

Our goal is to design a program that would show us on a map the locations of the capitals of all 48 contiguous US states and show us how we can travel from any capital to another.

This problem can be abstracted to finding a path in a network of nodes connected with links — known in the combinatorial mathematics as a graph traversal problem. You have already seen this problem in your assignments at least once.

The Data

To provide real examples of data the provided code includes the (incomplete) definitions of the class `City` and the class `State`.

1. Download the code for **Lab 10** and build the project **USmap**.
2. Download the file of state capitals *caps.txt*.
3. The project contains an implementations of the `Traversal` interface by the class `InFileCityTraversal` that allows you to read a file of `City` data. The code in the `Examples` class saves the city data generated by the `InFileCityTraversal` into an `ArrayList`.

Run the code with some of the city data files.

4. The `Examples` class contains examples of the data for three New England states (ME, VT, MA) and their capitals. Add the data for the remaining three states: CT, NH, RI. Initialize the lists of neighboring states for each of these states. Do not include the neighbors outside of the New England region.
5. Finally, look at the definition of the method `toString` both in the `City` class and in the `State` class. The class `Object` defines such method for all classes, but it is of little use. Comment out the `toString` method in the class `City` and see what happens when you run the code.

From now on, you should define a `toString` method for every class you define, making sure the resulting `String` is readable and the fields are clearly identifiable.

We now have all the data we need to proceed with learning about hash codes, equals, and `JUnit`.

Using HashMap

The class `USmap` contains only one field and a constructor. The field is defined as:

```
HashMap<City, State> states = new HashMap<City, State>();
```

The `HashMap` is designed to store the values of the type `State`, each corresponding to a unique key, an instance of a `City` — its capital.

Note: In reality this would not be a good choice to the keys for a `HashMap` — we do it to illustrate the problems that may come up.

1. Go to Java documentation and read what it says about `HashMap`. The two methods you will use the most are `put` and `get`.
2. Define the method `initMap` in the class `Examples` that will add to the given `HashMap` the six New England states.
3. Test the effects by verifying the size of the `HashMap` and by checking that it contains at least three of the items you have added. Consult *Javadocs* to find the methods that allow you to inspect the contents and the size of the `HashMap`.

Understanding HashMap

We will now experiment with `HashMap` to understand how changes in the `equals` method and the `hashCode` method affect its behavior.

1. Define a new `City` instance `boston2` initialized with the same values as the original `boston`. Now put the state `MA` again into the table, using `boston2` as the key. The size of the `HashMap` should now be 7.
2. Now define the `equals` method in the class `City` that makes sure the two cities have the same name, state, zip code, and the same latitude and longitude. Use the given helper method `sameDouble` to compare the last two fields. Start the method with:

```
public boolean equals(Object obj){
    City temp = (City)obj; ...
```

If the given object is of the type that cannot be cast to `City` the method will fail at runtime with the `ClassCastException`.

Now run the same experiment as above. The resulting `HashMap` still has size seven. Even though we think the two cities are equal, they produce a different hash code.

3. Now hide the `equals` method (comment it out) and define a new `hashCode` method by producing an integer that is the sum of the hash codes of all the fields in the `City` class.

Now run the same experiment as above. The resulting `HashMap` still has size seven. Even though the two cities produce the same hash code, the `HashMap` sees that they are not equal and does not confuse the two values.

4. Now un-hide the `equals` method so that two `City` objects that we consider to be the same produce the same hash code.

When you run the experiment again you will see that the size of the `HashMap` remains the same after we inserted `Massachusetts` with the `boston2` key.

Note: Read in "Effective Java" a detailed tutorial on overriding `equals` and `hashCode`.

Part 2: Introducing JUnit

You will now rewrite all your tests using the `JUnit4`. In the **File** menu select **New** then **JUnitTestCase**. The tests for each of the methods will then become one test case similar to this one:

```
/**
 * Testing the method toString
 */
public void testToString(){
    assertEquals("Hello: 1\n", this.hello1.toString());
    assertEquals("Hello: 3\n", this.hello3.toString());
}
```

We see that `assertEquals` calls are basically the same as the test methods for our test harnesses, they just don't include the names of the tests. Try to see what happens when some of the tests fail, when a test throws an exception, and finally, make sure that at the end all tests succeed.

- Add a method that determines whether the city is South of the given latitude. Run the tests using the JUnit.
- Add a method that determines whether this city is in the same state as the given city. Run the tests using the JUnit.

Ask for help, try things — make sure you can use JUnit, so you will not run into problems when working on the assignment and the final project.

Warning

Try to get as much as possible during the lab. Ask questions when you do not understand something. *The first part of the next assignment asks you to hand in a complete solution to this lab.*

Stack, Queue, Priority Queue, LinkedList; Vector

Look up the documentation for the following Java classes and interfaces: Stack, Queue, PriorityQueue, List, LinkedList and Vector. Identify which of them represent interfaces, which represent abstract classes, and which provide a complete implementation that you can use in your program. Draw a class diagram that shows the relationship between these classes and interfaces.